

Residential Soundproofing

“Quality living with minimal noise”

Construct high performance soundproof walls, floors and ceilings to minimise noise transmission and reduce the low frequency sound which is the most difficult to overcome.

Add to the quality and feel of a good home and exceed expectations for common walls, home theatre rooms, sheds, entertaining areas and road noise.

Use high performance acoustic materials for the best soundproofing over all frequencies. A poor system becomes an expensive re-fit along with the inconvenience once walls and floors have been built.

R2.5/32 - high performance polyester acoustic batts with an NRC 1+ (1 = 100%) to provide good absorption over all frequencies being 32kg density plus an R2.5 thermal rating. Install in the ceiling to overcome flanking issues and being polyester will not irritate or have OH&S issues when fitting.

8kg Wavebar barrier - reduce noise transfer with Rw 51 to 59 (decibel reduction) to achieve a good reduction and less transfer of the lower frequencies.

Acoustic underlay- reduce impact noise with **Silentstep** for heavy duty multi-level buildings, **TimberCushion** for timber and **AcustiCushion** for carpets

13mm Soundcheck - Gyprock to reduce noise transfer. 13kg/m² density with a dense core to reduce noise transfer through walls.

Soundlag – acoustic lagging for waste pipe soundproofing.

Acoustic panels - absorb reverberation and reduce the amount of noise transfer to other rooms. Ceiling tiles and wall panels to suit needs and décor.

Australian made and tested with no toxic chemicals!



ABN 32 768 939 131

Peter 0468 356 600

info@thesilencer.com.au

www.thesilencer.com.au